

Road vehicle descriptor

Information included in the Road Vehicle Descriptor (RVD) is supplied by the applicant for a vehicle type approval. This information is made available by the department for download to assist in defining the variants covered by the application or approval.

This downloaded version of the RVD is current on the date of the download identified below.

This information has not been verified or approved by the department. The department makes no statements or representations about the accuracy or completeness of this information.

Document Generated: 2024/05/16 12:39

General information

Vehicle type approval number:	VTA-062143 20230630
Make:	TEEBRO Toyota
Model:	Landcruiser J7 LS
Category:	N - Goods Vehicles

Secure vehicle identifier / vehicle plate details

Location:	Passenger Side "B" Pillar
------------------	---------------------------

List of variant(s)

Variant information for VDJL79R-TJMNYQ3-3900LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	2
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0

Gross vehicle mass (kg):	3900
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name
Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
JTELVL3J900123456

Variant information for VDJL79R-TJMRYQ3-3900LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	2
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	3900
Maximum towing mass (braked trailer) (kg):	3500

Maximum towing mass (non-braked trailer) (kg):	750
---	-----

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name
Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
JTELVL1J500123456

Variant information for VDJL79R-TJMNYQ3-4200LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	2
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	4200
Maximum towing mass (braked trailer) (kg):	3500

Maximum towing mass (non-braked trailer) (kg):	750
---	-----

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name
Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
JTELVL3J900123456

Variant information for VDJL79R-TJMRYQ3-4200LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	2
No. of doors side:	2
No. of doors rear:	0
Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	4200
Maximum towing mass (braked trailer) (kg):	3500

Maximum towing mass (non-braked trailer) (kg):	750
---	-----

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name
Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
JTELV1J500123456

Variant information for VDJL79R-DKMRYQ3-3900LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	5
No. of doors side:	4
No. of doors rear:	0

Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	3900
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name

Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Optional (O)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Optional (O)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
--

JTEBVL1J000123456

Variant information for VDJL79R-DKMRYQ3-4200LS

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	5
No. of doors side:	4
No. of doors rear:	0

Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	4200
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3180
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name

Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Optional (O)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Optional (O)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
--

JTEBVL1J000123456

Variant information for VDJL79R-DKMRYQ3-3900LS+300

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	5
No. of doors side:	4
No. of doors rear:	0

Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	3900
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3480
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name

Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Optional (O)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Optional (O)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
--

JTEBVL1J000123456

Variant information for VDJL79R-DKMRYQ3-4200LS+300

Front 3/4 image:



Rear 3/4 image:



Variant details

Body style:	CAB/CHASSIS
NSW body code:	Cab and Chassis
Seating options:	5
No. of doors side:	4
No. of doors rear:	0

Axle code:	2 Axles, single tyres front and rear
Tare mass (kg):	0
Gross vehicle mass (kg):	4200
Maximum towing mass (braked trailer) (kg):	3500
Maximum towing mass (non-braked trailer) (kg):	750

Major Dimensions

Vehicle length (mm):	0
Vehicle width (mm):	0
Vehicle height (mm):	0
Wheelbase (mm):	3480
Running clearance (mm):	0

Engine details

Engine name	Variant availability type	Mass variation amount
Engine - A	Standard (S)	

Service Brake

Service brake name	Variant availability type
Brake System - A	Standard (S)

Transmission

Transmission name	Variant availability	Variant amount
Transmission - A	Standard (S)	

Tyre and Rim

Tyre and rim name	Variant availability type
Tyre and Rim Combination - a	Std Front and Rear (SB)
Tyre & Rim Combination - j	Opt Front and Rear (OB)
Tyre & Rim Combination - k	Opt Front and Rear (OB)
Tyre & Rim Combination - l	Opt Front and Rear (OB)
Tyre & Rim Combination - m	Opt Front and Rear (OB)
Tyre & Rim Combination - n	Opt Front and Rear (OB)
Tyre & Rim Combination - o	Opt Front and Rear (OB)
Tyre & Rim Combination - p	Opt Front and Rear (OB)
Tyre & Rim Combination - q	Opt Front and Rear (OB)
Tyre & Rim Combination - r	Opt Front and Rear (OB)
Tyre & Rim Combination - s	Opt Front and Rear (OB)
Tyre and Rim Combination - b	Opt Front and Rear (OB)
Tyre & Rim Combination - t	Opt Front and Rear (OB)
Tyre & Rim Combination - u	Opt Front and Rear (OB)
Tyre & Rim Combination - v	Opt Front and Rear (OB)
Tyre & Rim Combination - w	Opt Front and Rear (OB)
Tyre & Rim Combination - x	Opt Front and Rear (OB)
Tyre & Rim Combination - y	Opt Front and Rear (OB)
Tyre & Rim Combination - z	Opt Front and Rear (OB)
Tyre & Rim Combination - aa	Opt Front and Rear (OB)
Tyre and Rim Combination - c	Opt Front and Rear (OB)
Tyre & Rim Combination - d	Opt Front and Rear (OB)
Tyre & Rim Combination - e	Opt Front and Rear (OB)
Tyre & Rim Combination - f	Opt Front and Rear (OB)
Tyre & Rim Combination - g	Opt Front and Rear (OB)
Tyre & Rim Combination - h	Opt Front and Rear (OB)
Tyre & Rim Combination - i	Opt Front and Rear (OB)

Suspension

Suspension name

Suspension Configuration - a

Standard equipment or options

Name	Variant availability type
Air conditioning	Standard (S)
Antilock brakes	Standard (S)
Central locking	Optional (O)
Driver's airbag	Standard (S)
Passenger's airbag	Standard (S)
Power windows	Optional (O)

Typical vehicle identification numbers (VINs)

Vehicle identification number (VIN)
--

JTEBVL1J000123456

Typical vehicle identification number (VIN) details

VIN:	JTEBVL1J000123456
Location:	11-P-8

Variant
VDJL79R-DKMRYQ3-3900LS
VDJL79R-DKMRYQ3-4200LS
VDJL79R-DKMRYQ3-3900LS+300
VDJL79R-DKMRYQ3-4200LS+300

VIN:	JTEVLV3J900123456
Location:	11-P-8

Variant
VDJL79R-TJMNYQ3-3900LS
VDJL79R-TJMNYQ3-4200LS

VIN:	JTELV1J500123456
Location:	11-P-8

Variant
VDJL79R-TJMRYQ3-3900LS
VDJL79R-TJMRYQ3-4200LS

Engine specifications

Engine - A

Motive power:	Diesel (D)
Configuration:	V configuration 8 cylinders (V8)
Net engine power (kW):	151.00
Net engine power (rpm):	3400
Capacity (cc):	4461.00
Fuel injection type:	Multipoint injection (MPI)
Induction type:	Turbo Charged (TC)
Stroke:	4.00000
Typical engine number:	1VD 0123456
Location:	5-I-6,2-K-13

Variant(s) this engine is applicable and the mass variation

Variant	Mass variation (kg) - positive or negative variation from tare weight	Mass variation amount
VDJL79R-TJMNYQ3-3900LS	Standard (S)	
VDJL79R-TJMRYQ3-3900LS	Standard (S)	
VDJL79R-TJMNYQ3-4200LS	Standard (S)	
VDJL79R-TJMRYQ3-4200LS	Standard (S)	
VDJL79R-DKMRYQ3-3900LS	Standard (S)	
VDJL79R-DKMRYQ3-4200LS	Standard (S)	
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)	
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)	

Service brake specifications

Brake System - A

Actuation type:	Hydraulic (H)
Power assisted:	Vacuum (VAC)

Front

Type:	Disc Ventilated (DIV)
Diameter (mm):	322
Width (mm):	32

Rear

Type:	Disc Ventilated (DIV)
Diameter (mm):	312
Width (mm):	18

For which variant(s) is the service brake applicable and how is it available?

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMRYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-TJMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Standard (S)
VDJL79R-DKMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)

Transmission data specifications

Transmission - A

Transmission type:	Manual All WD (MAWD)
Forward gears:	5

Variant(s) this transmission is applicable to, and the mass variation

Variant	Mass variation (kg) – positive or negative variation from tare weight	Variation amount
VDJL79R-TJMNYQ3-3900LS	Standard (S)	
VDJL79R-TJMRYQ3-3900LS	Standard (S)	
VDJL79R-TJMNYQ3-4200LS	Standard (S)	
VDJL79R-TJMRYQ3-4200LS	Standard (S)	
VDJL79R-DKMRYQ3-3900LS	Standard (S)	
VDJL79R-DKMRYQ3-4200LS	Standard (S)	
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)	
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)	

Tyre and rim specifications

Tyre & Rim Combination - d

Tyre designation:	315/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - e

Tyre designation:	315/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - f

Tyre designation:	315/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - g

Tyre designation:	295/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - h

Tyre designation:	295/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - i

Tyre designation:	295/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - j

Tyre designation:	285/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - k

Tyre designation:	285/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - I

Tyre designation:	285/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - m

Tyre designation:	315/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - n

Tyre designation:	315/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - o

Tyre designation:	315/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - p

Tyre designation:	285/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - g

Tyre designation:	285/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - r

Tyre designation:	285/75 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - s

Tyre designation:	305/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - t

Tyre designation:	305/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - u

Tyre designation:	305/70 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - v

Tyre designation:	285/75 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - w

Tyre designation:	285/75 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - x

Tyre designation:	285/75 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - y

Tyre designation:	305/70 R16
Rim size and profile:	16x8
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - z

Tyre designation:	305/70 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre & Rim Combination - aa

Tyre designation:	305/70 R16
Rim size and profile:	16x8
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre and Rim Combination - a

Tyre designation:	35/12.5 R17
Rim size and profile:	17x9
Rim offset (mm):	Positive offset (+)
Rim offset amount (mm):	0
Front wheel track (mm):	1555
Rear wheel track (mm):	1555

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Std Front and Rear (SB)
VDJL79R-TJMRYQ3-3900LS	Std Front and Rear (SB)
VDJL79R-TJMNYQ3-4200LS	Std Front and Rear (SB)
VDJL79R-TJMRYQ3-4200LS	Std Front and Rear (SB)
VDJL79R-DKMRYQ3-3900LS	Std Front and Rear (SB)
VDJL79R-DKMRYQ3-4200LS	Std Front and Rear (SB)
VDJL79R-DKMRYQ3-3900LS+300	Std Front and Rear (SB)
VDJL79R-DKMRYQ3-4200LS+300	Std Front and Rear (SB)

Tyre and Rim Combination - b

Tyre designation:	35/12.5 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	12
Front wheel track (mm):	1579
Rear wheel track (mm):	1579

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Tyre and Rim Combination - c

Tyre designation:	35/12.5 R17
Rim size and profile:	17x9
Rim offset (mm):	Negative offset (-)
Rim offset amount (mm):	25
Front wheel track (mm):	1605
Rear wheel track (mm):	1605

Variant(s) this tyre and rim is applicable to, and how it is available

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-TJMNYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-TJMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-3900LS+300	Opt Front and Rear (OB)
VDJL79R-DKMRYQ3-4200LS+300	Opt Front and Rear (OB)

Suspension data specifications

Suspension Configuration - a

Vertical measurements	Front (mm)	Rear (mm)
Vertical measurement of wheel centre to top of wheel arch opening at "Unladen Mass"	0	0
Vertical measurement of wheel centre to top of wheel arch opening at full bump	0	0
Minimum acceptable vertical measurement of wheel centre to top of wheel arch		

Variant(s) this suspension is applicable to, and how it is available

Variant
VDJL79R-TJMNYQ3-3900LS
VDJL79R-TJMRYQ3-3900LS
VDJL79R-TJMNYQ3-4200LS
VDJL79R-TJMRYQ3-4200LS
VDJL79R-DKMRYQ3-3900LS
VDJL79R-DKMRYQ3-4200LS
VDJL79R-DKMRYQ3-3900LS+300
VDJL79R-DKMRYQ3-4200LS+300

Standard equipment or options which may affect ADR compliance

Air conditioning

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMRYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-TJMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Standard (S)
VDJL79R-DKMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)

Antilock brakes

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMRYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-TJMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Standard (S)
VDJL79R-DKMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)

Power windows

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Optional (O)
VDJL79R-DKMRYQ3-4200LS	Optional (O)
VDJL79R-DKMRYQ3-3900LS+300	Optional (O)
VDJL79R-DKMRYQ3-4200LS+300	Optional (O)

Driver's airbag

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMRYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-TJMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Standard (S)
VDJL79R-DKMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)

Passenger's airbag

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMRYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-TJMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Standard (S)
VDJL79R-DKMRYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS+300	Standard (S)
VDJL79R-DKMRYQ3-4200LS+300	Standard (S)

Central locking

Variant	Variant availability type
VDJL79R-TJMNYQ3-3900LS	Standard (S)
VDJL79R-TJMNYQ3-4200LS	Standard (S)
VDJL79R-DKMRYQ3-3900LS	Optional (O)
VDJL79R-DKMRYQ3-4200LS	Optional (O)
VDJL79R-DKMRYQ3-3900LS+300	Optional (O)
VDJL79R-DKMRYQ3-4200LS+300	Optional (O)

Remarks

SSM vehicle for the purpose of GVM upgrade to FSM VTA-060702. Revised GVM includes 3900 kg and 4200 kg variants. All Variants group axle rating front up to 1650 kg, all variants have a group axle rating rear up to 2800 kg. Vehicle category remains NB1 cab chassis. The track is corrected by 100mm from standard Toyota 70 Series rear axles. Modifications common to all variants are as follows: Upgrade of front and rear suspension to higher rated components, upgrade of rear differential to a heavy duty unit. 50-100mm Suspension Spring lift and larger wheel / tyre package, also includes replacement radius arms to support increased suspension height. Brake booster upgrade included for all vehicle variants. Appropriate speed rated driveshaft for chassis extension variants. The variants of this SSM are based on the corresponding variants from the base vehicle, manufactured by Toyota under VTA-060702. VD JL79R-DKMRYQ3-xxxxLS as shown on this RVD are based VD JL79R-DKMRYQ3 (Variant 4) of the FSM. VD JL79R-TJMNYQ3-xxxxLS as shown on this RVD are based VD JL79R-TJMNYQ3 (Variant 5) of the FSM. VD JL79R-TJMRYQ3-xxxxLS as shown on this RVD are based VD JL79R-TJMRYQ3 (Variant 6) of the FSM. Additional VD JL79R-DKMRYQ3 variant of the base vehicle includes a 300mm chassis extension shown as VD JL79R-DKMRYQ3-xxxxLS + 300. "0" values provided in lieu of N/A for vehicle length, width, height, running clearance, and weight of cab chassis variants. Such values are to be confirmed by the bodybuilder. Refer attached tyre placard information for further detail. A QR code to be attached to OEM service manual for additional fitment and servicing for undertaken modifications.